



## SPECIFICATION

<b>Model</b>	<b>HT812</b>	
<b>Power</b>	Power Adapter Voltage	Input: 110-240V/AC 50-60Hz 5
	The maximum power supply machine	100W
<b>Protection level</b>	Mould	+/-4KV
	Differential mode	+/-1KV
<b>Network Connector</b>	Network Port	1~8 port: :10/100Mbps PoE Ethernet LAN port WAN1/WAN2 port : 10/100/1000Mbps Ethernet WAN port
	Transmission Distance	Extend switch is default OFF, state(1~8 port): 100m Extend switch is ON, state:(1~8 port): 200m WAN1/WAN2 port: 100m
	Transmission Medium	Cat5/5e/6 standard network cable
<b>Network Switch</b>	Network Standard	IEEE802.3/10BASE-T
		IEEE802.3u/100BASE-TX
		IEEE802.3x Flow Control, IEEE802.3az
	Maximum Frame Size	1536 Bytes
	MAC address list	2K
	Backplane bandwidth	1Gbps
	PoE Standard	IEEE802.3af/at
<b>Power Over Ethernet</b>	PoE Power Supply Type□	End-Span(4/5+;7/8-)
	PoE Power Consumption	af,at Adaptive (every port)
<b>LED Status Indicator</b>	PoE Ethernet	When the PoE is powered, 1-8 LEDs are green
		When accessing Ethernet, ports 1-8 are yellow
<b>Environmental</b>	Working temperature	0°C ~55°C
	Storage temperature	-40°C ~70°C
	Working humidity	10%-90% non-condensing
	Storage humidity	5%-95% non-condensing
<b>Mechanical</b>	Dimension (L x W x H) mm	220*140*40
	Weight	1.4KG
	Material	SECC
	Color	Dark grey
<b>Stability</b>	MTBF	>30000h