

Longse



SPECIFICATION

| | | | |
|------------------------|--|----------------|----------------|
| Model NO. | LBH30HTC200FEH | LBH30CHT200FEH | LBH30THC200FEH |
| Video Output Mode | AHD/TVI: 5M@20fps/12.5fps, 4M@30fps, 2M@30fps; CVI: 4M@30fps, 2M@30fps | | |
| Camera | | | |
| Image Sensor | 1/3" CMOS Sensor | | |
| Image Resolution | 5M:2592*1944 4M:2560*1440 2M:1920*1080 | | |
| TV System | PAL/NTSC | | |
| Electronic Shutter | AUTO | | |
| Scanning System | Progressive Scan | | |
| Lens | | | |
| Focus Length | 3.6mm | | |
| Focus Control | Fixed | | |
| Lens Type | Fixed | | |
| Night Vision | | | |
| IR Cut Filter | YES | | |
| Infrared LED | 14μ x 20PCS | | |
| Infrared Distance | 25M | | |
| IR Status | AGC Auto Control | | |
| Camera Features | | | |
| Starlight | / | | |
| Day/Night | YES | | |
| OSD Menu | YES | | |
| WDR | DWDR | | |
| UTC | YES | | |
| Noise Reduction | DNR | | |
| White Balance | AUTO / MANUAL | | |
| Gain Control | AUTO | | |
| General | | | |
| Housing | Metal, IP67 | | |
| Bracket | YES | | |
| Operation Temperature | -10°C ~ +60°C RH95% Max | | |
| Storage Temperature | -20°C ~ +60°C RH95% Max | | |
| Power Source | DC12V±10%, 700mA | | |
| Dimension | 157(W) x 70(H) x 66(D)mm | | |
| Weight | 650g | | |